



COAL TAR PAVEMENT SEALER

BASIC USES

Coal Tar Concentrate Pavement Sealer is designed for seal coating to beautify and protect all types of asphalt pavement surfaces including parking lots, airports, driveways, shopping malls, roadways, and more provides superior fuel resistance.

COVERAGE

40 to 70 square feet per gallon depending on age, pavement porosity, and method of applicaton.

COLORS AVAIABLE

BLACK

* Colors may vary slightly from actual product.

DESCRIPTION

Coal Tar Sealer Concentrate Pavement Sealer is clay stabilized, fuel resistant coal tar emulsion pavement sealer designed to protect and beautfy asphalt pavement. Coal Tar Concentrate Pavement Sealer is formulated to be job mixed with water.

ADVANTAGES

- Deep, Rich Black Color
- Oil and Fuel Resistant
- Reduced Fume Formulaton for User Friendly Applicaton

Having your driveway seal coated can pro long the life expectancy of the asphalt. It protects it against the elements like rain, snow, ice and harmful UV rays. It also protects it from gas, oil, antifreeze and any other unexpected spills that could eat away your driveway and soften it up to the point of stones loosing up and start to pop up. If anything does leak on to your driveway it will eat away at the sealer first instead of your driveway. Sealer also keeps your driveway looking new and clean.

SURFACE PREPARATION

New asphalt surfaces must cure a minimum of four weeks under ideal weather conditons before applicaton. Surface must be clean and free from all loose material, dirt, and dust. Cracks should be filled with Hot Pour or Cold Applied crack fillers.

MIXING PROCEDURES

For optpum results, mix Coal Tar Concentrate Pavement Sealer in accordance with the following mix design (based on 100 gallons for ease of calculaton):

Coal Tar Concentrate Pavement Sealer: 100 gallons **Water:** 20 – 30 gallons



Angelo's
PAVING, Inc

38 Poplar Ave. West Long Branch, NJ 07764
Telephone: 732-741-8965 Fax: 732-222-8283

COAL TAR PAVEMENT SEALER

ENVIRONMENTAL CONSIDERATIONS

Coal Tar Concentrate Pavement Sealer does not contain Asbestos. Coal Tar Concentrate is an environmentally friendly water based pavement sealer.

IMPORTANT

Temperatures must be above 50°F both during application and for a period of at least 24 hours after application.
Do not apply when rain is imminent or forecast.

APPLICATION

Angelo's Paving Inc, Applies by Broom, NOT SPRAYED. Allow 24 TO 36 hours before parking cars or allowing traffic to resume.

After your driveway has been sealed with Coal Tar Concentrate Pavement Sealer. The driveway sealer needs 24 to 36 hrs to fully dry. Please stay off your driveway for a minimum of 24 to 36 hrs. (No walking, driving, pets on your driveway). Please turn off all water sprinklers for the same amount of time.



WE USE SEALMASTER PRODUCTS